

| <b>FURNISHING OF CENTRAL BANK, ALLEPPEY BRANCH</b> |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |            |             |             |               |
|----------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------|-------------|-------------|---------------|
| <b>Sl.No</b>                                       | <b>Description</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | <b>Qty</b> | <b>Unit</b> | <b>Rate</b> | <b>Amount</b> |
| <b>A</b>                                           | <b>BANKING AREA</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |            |             |             |               |
| <b>1</b>                                           | <b>ACP covering for Rolling shutter</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             |            |             |             |               |
|                                                    | Supplying and fixing Aluminium framework using 25mm x50 mm x1.5 mm square aluminium sections in the front, sides and bottom of rolling shutter and covering with 3mm ACP of approved colour on the sides that are visible. The bottom panel should be hinged and openable for maintenance of Rolling Shutters. and rates shall be including all accessories hinges, handles, ballcatches, etc., complete.                                                                                                                                           | 9.00       | Sq. Mts.    |             | 0.00          |
| <b>2</b>                                           | <b>Frameless Entrance Door - 12mm thick toughened glass Double Leaf Door (185 x 210) and Single Leaf Door to Managers Cabin(90 x 210)</b>                                                                                                                                                                                                                                                                                                                                                                                                           |            |             |             |               |
|                                                    | Providing and fixing 210 cm high 12mm thick toughened glass (SAINT GOBAIN or MODIGUARD) Entrance Door using patch fittings. Rubber beading to be given to the doors.Doors to be provided with 25mm dia x 425mm SS handles(H type) , Glass door to door Patch Lock with strike box (without glass cutting) and heavy duty floor spring with double swing control (Dorma 75V or equivalent) supporting 80 kg. Vinyl Film strips of frosted glass finish to be pasted on the glass as per design along with Logo of Central Bank Pull push plates etc. | 6.00       | Sq. Mts.    |             | 0.00          |
| <b>3</b>                                           | <b>Frameless fixed glazing (12mm thick toughened glass) in the front of Banking area and front of Managers Cabin.</b>                                                                                                                                                                                                                                                                                                                                                                                                                               |            |             |             |               |

| Sl.No    | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     | Qty   | Unit     | Rate | Amount |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|----------|------|--------|
|          | Providing and fixing 210 cm high 12mm thick toughened glass (SAINT GOBAIN or MODIGUARD) fixed with patch fittings. Vinyl Film strips of frosted glass finish to be pasted on the glass as per design along with Logo of Central Bank.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 21.00 | Sq. Mts. |      | 0.00   |
| <b>4</b> | <b>Partly glazed Partition for the side of Manager's Cabin including Door</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |       |          |      |        |
|          | Providing and fixing Double skin partitions upto bottom of true ceiling with glazing using aluminium frame work of 50mmx50mmx2mm (2 ft'c/c) bothways covered on both sides with 6 mm BWR plywood (IS 303 grade) finished with 1mm lamination of approved colour & pattern as per the design given in the drawing. 8mm thick toughened glass to be fixed at a height of 90 cms from FFL upto 210 cms. The glass is to be fixed with 1/2" x1 1/2" beechwood reapers polished to finish with PU coating. Doors to be provided with heavy duty Door closers (EBCO/Godrej /DORMA ), Cylindrical lock ( EBCO/Godrej /DORMA), SS Tower Bolt, Door stopper,SS Hinges etc. Complete. Vinyl Film strips of frosted glass finish to be pasted as per design on the glass. (Note: Measurements will be taken only upto false ceiling level) | 10.00 | Sq. Mts. |      | 0.00   |
| <b>5</b> | <b>Double skinned &amp; partly glazed low height partition for CashCounter, with powder coated Aluminium expanded Deco grill on the top.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |       |          |      |        |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Qty   | Unit     | Rate | Amount |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|----------|------|--------|
|       | Fabricating and fixing partly glazed partitions of double skin type on side and back of the Cash Counters of 210 cm height made of 50mmx50mmx2mm (2 ft'c/c) aluminium frames covered on both sides with 6mm BWR plywood (IS 303 grade)pasted with 1mm thk laminate, and 8mm glass panels inserted within.The glass panels shall be in two pieces and have a voice gap of 5cms in the middle and fixed with beachwood reapers.The facing edges & top of partition to be pasted with 1mm thk laminate. The 12mm front glass shall be measured as a separate item. All edges of glass to be polished. The top of the cabin shall be enclosed using white powder coated Aluminium Deco grill fixed to the partitions firmly and neatly using suitable aluminium sections. | 10.00 | Sq. Mts. |      | 0      |
|       | The side partitions shall have openings to fix 30cms x 40cms x 8cms wooden tray for passing transaction slips and . The cash counter shall be provided with a 70 cm wide door fixed with SS hinges , SS tower bolt, Godrej night latch, SS handles and door stopper etc. All wooden beadings shall be scraped well and sand papered to smooth finish after applying sealer. The wooden members shall then be applied with two coats of satin finish polyurethane polish. Vinyl Film strips of frosted glass finish to be pasted as per design on the fixed glass.                                                                                                                                                                                                     |       |          |      |        |
| 6     | 12 mm glass in front of Cash, & gold                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |       |          |      |        |

| Sl.No    | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Qty   | Unit     | Rate | Amount |
|----------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|----------|------|--------|
|          | 12mm glass in front of <b>Cash</b> 65cms high above the ledge for cash/swc and for <b>Gold</b> 45 cms high above table height for supervisor & gold. The Cash/SWC glass shall be of two pieces horizontally and shall be fixed with a horizontal gap in between for carrying voice. This shall be fixed to the side partitions and table tops with D brackets. An opening 30cms x 15 cms for transactions shall be provided in the front of the lower piece of glass. Vinyl Film strips of frosted glass finish to be pasted as per design. All edges of glass to be polished to finish. | 2.00  | Sq. Mts. |      | 0.00   |
| <b>7</b> | <b>Low Height -Plywood and glass between seats and for FOREX cabin of 70mm thickness.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |       |          |      |        |
|          | Plywood and glass partition fixed between seats in the Counter and also FOREX cabin. Solid portion to be fabricated from Rectangular Aluminium sections of 2 " x 1"size covered with 12mm Plywood on both sides and pasted with laminate on both sides. The edges to be finished with Beechwood. 12mm glass as per drawing to be fixed to the counter with the vinyl of bank logo and the vertical solid partition using SS brackets .                                                                                                                                                   | 17.00 | Sq. Mts. |      | 0.00   |
| <b>8</b> | <b>Floating shelf for trophy in Managers Room ( 150cms x 20 cms, l x w)</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |       |          |      |        |
|          | Providing 80mm thick floating shelves of size 150 cms length and 20 cms width suitably fixed to the Backwall in Managers cabin                                                                                                                                                                                                                                                                                                                                                                                                                                                           | 2.00  | nos      |      | 0.00   |
| <b>9</b> | <b>Bison Panel partition upto bottom of True ceiling</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |       |          |      |        |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          | Qty   | Unit     | Rate | Amount |
|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|----------|------|--------|
|       | Providing & fixing Rectangular Aluminium sections of 2 " x 1" size at 20" - 22" c/c and both sides covered with 6mm thick Bison Panel Cement boards including additional frames for fixing doors. The partition should withstand its weight. The joints shall be sealed with tape and finished with putty to appear jointless. The partition shall be finished with good quality emulsion paint over a layer of putty to be smoothly sanded , and a coat of primer etc.complete.The partition shall be extended upto true ceiling or bottom of beam. | 12.00 | Sq. Mts. |      | 0.00   |
| 10    | <b>Solid partition including Doors</b> upto bottom of True ceiling.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  | 8.00  | Sq. Mts. |      | 0.00   |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              | Qty   | Unit     | Rate | Amount |
|-------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------|----------|------|--------|
|       | Providing and fixing Double skin partitions upto bottom of true ceiling using aluminium frame work of 50mmx50mmx2mm (2 ft'c/c) bothways covered on both sides with 6 mm BWR plywood (IS 303 grade) finished with 1mm lamination of approved colour & pattern as per the design given in the drawing. Necessary holes must be made in the frame sections to run the wires, computer cables wherever necessary. Similarly, necessary cuttings to be made in the plywood surface to fix switch boxes of electrical, telephone sockets, computer information outlets etc. Additional stiffners using 18 mm thick 303 Grade (BWR) plywood shall be made for fixing flush doors..Doors to be provided with Vision Glass 6mm thick of 30cms x 90 cms, heavy duty Door closers (EBCO/Godrej /DORMA ), cylindrical lock ( EBCO/Godrej /DORMA) and 304 grade SS Pull handle, SS Tower bolts as per instructions etc. Complete. Vinyl Film strips of frosted glass finish to be pasted as per design on the glass. (Note: Measurements will be taken only upto false ceiling level) |       |          |      |        |
| 11    | <b>Composite Partition including Doors (one side plywood with laminate and one side Cement Board painted)</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            | 95.00 | Sq. Mts. |      | 0.00   |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | Qty | Unit | Rate | Amount |
|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|------|------|--------|
|       | Providing & fixing composite partitions as per design with Rectangular Aluminium sections of 50mm x 50mm x 2mm size provided at not more than 600 mm c/c both ways and covered on one side with 6 mm thick 303 Grade (BWR) Plywood and the other side 6 mm thick Cement board using self drilling screws between banking hall and back office area, etc. The partition should withstand its weight. The plywood surface shall be finished with 1mm thick laminate and the Joints between the Cement board shall be fixed with fiberglass joint mesh and finished with putty. The cement board shall be finished with 1 coat of cement primer , 1 coat of smoth putty and 2 coats of Interior Emulsion paint.                                |     |      |      |        |
|       | Provision for flush doors shall be considered wherever required. Additional stiffners using 18 mm thick 303 Grade (BWR) plywood shall be made for fixing flush shutters.Doors to be provided with Vision Glass 6mm thick of 30cms x 90 cms, heavy duty Door closers (EBCO/Godrej /DORMA ), cylindrical lock ( EBCO/Godrej /DORMA) , SS Tower bolts as per instructions etc. Complete. Vinyl Film strips of frosted glass finish to be pasted as per design on the glass. (The partition shall be erected upto 3" above the False Ceiling Level and the corner / and third vertical supports shall be anchored firmly to the RCC roof for support. However, only the exposed area below the False Ceiling shall be considered for payment.). |     |      |      |        |
| 12    | <b>Wicket gate 105 cms wide (75cms wide + 30cms wide) and 75 cms height.</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |     |      |      |        |

| Sl.No     | Description                                                                                                                                                                                                                                                                                                                                 | Qty  | Unit     | Rate | Amount |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|----------|------|--------|
|           | Wicket gate made out 18mm BWR plywood covered on both sides with laminate with edges finished with 6mm thick beechwood lipping. This shall be hinged to the counters on both sides (additional plywood panels Should be given in the counters for fixing hinges if necessary) Tower bolts to be provided for keeping the wicket gate closed | 1.00 | Sq. Mts. |      | 0.00   |
| <b>13</b> | <b>Column Cladding / wall panelling</b>                                                                                                                                                                                                                                                                                                     |      |          |      |        |
|           | Cladding the columns upto false ceiling height by fixing 25mm x 25mm x 1.5mm aluminium sections at 60cm spacing and covering with 8 mm BWR (IS 303 grade) plywood pasted with 1mm laminate as per drawing. For round columns , the circular shape to be made square with 50mm x 50mm Al sections in the corners for stability.              | 30   | Sq. Mts. |      | 0.00   |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Qty | Unit | Rate | Amount |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|------|------|--------|
| 14    | <b>BANKING COUNTERS &amp; FURNITURE</b> All Tables to be of 75cms height with 8mm glass top and to be made out of 19mm thick plywood (BWR IS 303) of Greenply/ Anchor/ approved make, covered with 1mm thick laminate of approved colour and design on the top and all visible sides.The front portion to have a 12mm thk plywood fixed as in the design provided and stuck with 1mm suede finish laminate of approved colour. All exposed edges of the plywood and the bottom of table shall have 12mm thick beachwood beading. The Inner sides to be painted to a smooth finish with good quality enamel paint (ICI/Dulux or eqlt.) over a coat of wood primer and 2 coats of putty sand papered to smooth finish.The wooden beading shall be smoothly sand papered and polished with satin finish polyurethane finish (Asian/Sleek), over two coats of sealer. |     |      |      |        |
|       | A 2" dia SS pipe to be provided as footrest . Wherever drawers are provided they should be made out of 12mm thick plywood, fixed on telescopic roller slides (EBCO / or approved make) and painted inside with 2 coats of enamel paint over 1 coat of smooth putty finish. A keyboard tray of size 70cms x 40 cms made of 18mm thick plywood covered with 1mm thick laminate moving on Telescopic sliders to be provided below table top at the centre. The glass top shall have all edges polished to finish with a cut out to fix a wire manager to draw cables.For drawer : Recessed Handle(Shutter Handle -Aluminium 3012 Square) (Ebco/eqlt).                                                                                                                                                                                                                |     |      |      |        |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Qty  | Unit | Rate | Amount |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|--------|
| a)    | <b>Chief Manager's table with 8mm tempered glass top of size of size 180 x 90 cms</b> made out of 19mm plywood with drawer unit on left side with 8mm tempered glass (St. Gobain / Modifloat ) with edge polished to be provided on top of the Table.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 | 1.00 | Nos  |      | 0.00   |
| b)    | <b>Cash tables with tempered glass top of size 150cms x 90 cms x 75cms .(l x b x h)</b> supported on 19mm BWR IS 303 grade plywood on both ends and 12mm plywood for the front. This shall have a keyboard tray and a drawer unit.The top shall also be of 19mm plywood pasted with 1mm thick laminate of approved colour. .An 8mm thick plain glass with edge polished to be provided over the laminated worktop. A transaction ledge also made of 19mm plywood laminated with 1mm thk laminate shall be provided above the counter with top of ledge at 107.5cms height from floor level on the customer side. The top drawer unit shall have separators made of 6mm plywood painted to smooth finish to store different denominations of currency. | 1.00 | Nos  |      | 0.00   |
| c)    | <b>Running counters of 75 cms width</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |      |      |      |        |
|       | Providing & fixing low counter with 19 mm thk BWR grade plywood finished with 1mm laminate on all visible areas for the supports and top. The front facia shall be of 12mm thk BWR plywood. Inside portions shall be finished with enamel paint after applying primer and putty finshed to smooth finish etc complete. Each seat shall have Keyboard trays, and SS footrest . The running counter shall have a 8mm glass top , with a wire manager fixed on the glass top to draw cables. The glass top shall have all edges neatly polished.                                                                                                                                                                                                         | 12.5 | Rmts |      | 0.00   |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                                                                                                      | Qty  | Unit | Rate | Amount |
|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|--------|
| d)    | Auditor/ Armed Guard Table : P/ F a Table having a size of 120cm x60cmx75cm ht. in 19mm thk BWR grade plywood finished in 1 mm thk specified laminate shade of approved brand as per the design/ drawing etc complete. The table shall have a 40cm wide drawer on one side at the top.Inside portions shall be finished with enamel paint after applying primer and putty finshed to smooth finish etc complete. | 2    | Nos  |      | 0.00   |
| e)    | <b>Dressing Table in strong room</b>                                                                                                                                                                                                                                                                                                                                                                             | 1.00 | nos  |      | 0.00   |
|       | Mirror of size 60cm x 90cm (bxh) with box type ledge of size 60cm x 25cm x 20cm (lxbxh) made out of 18mm BWR plywood to be fixed with full thread screw to the wall with a 8mm BWR plywood backing. All exposed sides to be laminated and edges fixed beachwood lipping.(refer detail in drawing )                                                                                                               |      |      |      |        |
| 15    | <b>Side Table</b>                                                                                                                                                                                                                                                                                                                                                                                                |      |      |      |        |
| a)    | Side table (105 x45) for Senior Manager of 75cms height consisting of lockable sliding shutters sliding on good quality rails.Recessed handle (Shutter Handle -Aluminium 3012 )(Ebco/eqlt) (Refer detail in drawing)                                                                                                                                                                                             | 1.00 | Nos  |      | 0.00   |
| b)    | Side table (75 x45) for Officers of 75 cms height consisting of drawers of 15cm height on the upper part and sliding lockable shutters below the drawers. Recessed handle (Shutter Handle - Aluminium 3012 )(Ebco/eqlt)(Refer detail in                                                                                                                                                                          | 4.00 | Nos  |      | 0.00   |

| Sl.No | Description                                                                                                                                                                                                                                                                                                | Qty  | Unit | Rate | Amount |
|-------|------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|--------|
| c)    | <b>Side table (120 x45)</b> for Cash of 75cms height consisting of lockable shutters on the left side and a drawer and shelf on the right side. Recessed handle (Shutter Handle -Aluminium 3012 )(Ebco/eqlt)(Refer detail in drawing)                                                                      | 1.00 | Nos  |      | 0.00   |
| 16    | <b>Pantry Counter</b>                                                                                                                                                                                                                                                                                      |      |      |      |        |
|       | Top and vertical supports to be made of 19mm plywood and top shall be provided with 19mm thk granite slab. Edges shall be rounded and polished. An intermediate shelf underneath shall be provided with 18mm plywood finished with laminate on the topside. Edge shall be finished with beechwood reapers. | 1    | Rmts |      | 0      |
| (b)   | <b>Dining Table In Pantry</b>                                                                                                                                                                                                                                                                              |      |      |      |        |
|       | Providing and fixing Dining table 75cms high made out of 19mm thk BWR Grade plywood for table top and supports with 1mm laminate top-and painted on all other sides. Edges shall be finished with beechwood reapers.                                                                                       |      |      |      |        |
|       | <b>180 x 60 cms</b>                                                                                                                                                                                                                                                                                        | 1.00 | No   |      | 0      |
|       | <b>100 x 60 cms</b>                                                                                                                                                                                                                                                                                        | 1.00 | No   |      | 0      |
| 17    | <b>Office Storage System</b>                                                                                                                                                                                                                                                                               |      |      |      |        |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                           | Qty | Unit | Rate | Amount |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|------|------|--------|
|       | Fabricating & fixing office storage system with 19mm plywood for sides and shutters & 6mm plywood backing, with edges fixed with 6mm beachwood lipping. The unit shall be provided with one or more intermediate shelf inside as per drawing. All exposed surfaces (inside and outside)of plywood shall be laminated with 1 mm thick laminate of approved colour and all exposed edges to be fixed with beachwood beading.All necessary fixtures like, Cupboard locks, Recessed handle (Shutter Handle -Aluminium 3512 )(Ebco/eqlt), brass hinges, and magnetic shutter catches etc to be provided. ( Measurement will be of area of the Front facia) |     |      |      |        |
| a)    | Low height in Managers Cabin ( 75 cms height)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 2   | Rmtr |      | 0      |
| b)    | Full height ( 210 cms height)                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | 22  | Rmtr |      | 0      |
| 18    | <b>Writing Table &amp; Slip Holder (Writing Top height at 105 cms.) 100 cms x 30 cms</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |     |      |      |        |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        | Qty  | Unit | Rate | Amount |
|-------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|------|------|--------|
|       | Providing and fixing wall mounted writing table cum slip storing ledge at the customer area at a suitable location. The writing table shall be wall mounted and have two boxes ( cheque drop/suggestion) extending below on two ends. (refer drawing)The unit shall be equipped with slip keeping slots made of 12mm plywood and writing surface at the top made up of 12mm glass .The side supports of the unit shall be made of 19mm thick plywood and backside with 8mm plywood and laminated with 1mm thick matt finished laminate. The unit shall be fixed to the wall at a height of 105 cm with wooden plugs, screws etc . Cheque drop box/ suggestion box provided below the writing ledge shall be provided with slots for dropping cheques and complaints and the shutters shall have 6mm vision glass panels and shutters to be fitted with SS handles, SS hinges, locks, etc complete. | 1.00 | Nos. |      | 0.00   |
| 19    | <b>Roller Blinds</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |      |      |      |        |

| Sl.No     | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Qty  | Unit     | Rate | Amount |
|-----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|----------|------|--------|
|           | Providing, fabricating and fixing vertical roller blinds of approved make preferably of “Vista Levelor” with a woven made acrylic coated fabric of 100% polyester of thickness 0.50 – 0.60 mm ( +/- 5% tolerance) with the main properties like resistance to Cracking & Fraying, dust repellence, UV proof and virtually maintenance free along with the Vista accessories of like Head rail , Roller tube Idler, Bottom rail, chain, matching colour installation brackets etc. including all fixtures and fittings of Vista like Rainbow curtain rods with electric resistance welded MS pipe having a corrugated virgin PVC extrusions reinforced to minimize friction, finials and along with standard anchoring arrangements etc. all complete done in workmanlike manner as per the approved design, colour and including necessary scaffolding as directed. | 2    | Sq. Mts. |      | 0.00   |
| <b>20</b> | <b>Notice board</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |      |          |      |        |
|           | Providing and fixing to the wall , notice board of size 1.80 m x 0.90 m, with 12 mm marine grade plywood as base with 12 mm soft board pasted on to it and covered with felt/ furnishing cloth of approved blue colour. The board shall have polished TW 1/2" x 1 1/4" beading all around including cost of all materials , labour charges etc complete                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | 1.00 | Nos      |      | 0.00   |
| <b>21</b> | <b>Bank's Logo Work on Main Door</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |      |          |      |        |
|           | Providing and Fixing Bank's Logo on glass doors, and glass panels                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   | 10   | Sq. Mts. |      | 0.00   |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Qty | Unit     | Rate | Amount |
|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----------|------|--------|
| 22.a) | <b>FALSE CEILING: Suspended stepped ceiling using Gypboard (refer drawing for false ceiling)</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                        |     |          |      |        |
|       | Providing and fixing stepped suspended false ceiling with Gypboard of 12.5mm thick to the suspended grid formed of perimeter channel of size 20 x 27 x30 mm (MF6A) and intermediate channel of size 45 x 15 x 0.9 mm (MF7)The G.I. Ceiling section of size 80 x26x0.5 mm (MF .5) shall be provided across the intermediate channel at intervals not more than 475 mm c/c at bottom and the same shall be fixed by GI connections clips of 2.64mm dia at integration points.The Ceiling channels shall be provided with a minimum overlap of 150mm at ends and fixed to the perimeter channels. Only horizontal measurements will be taken for bill calculation. Step/vertical area cost to be included. | 159 | Sq. Mts. |      | 0.00   |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                         | Qty | Unit | Rate | Amount |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|------|------|--------|
|       | The suspended strap hangers to be connected with G.I soffit cleat of size 37 x27x25x1.5 mm thick and to be fixed on to the roof slabs/beams by using metal expansion fasteners of 12.5 mm dia to a length of 35 mm.The suspender supporters shall be provided at intervals not more than 1200 mm c/c Additional perimeter channels have to be provided around the cut for light fitting A/C diffusers etc. Additional support for cut outs to be provided at no extra cost. The Gypboard sha;; be fised top the inder side of the suspended grid by using 25mm long dry wall screws. The joints shall be finished with joint paper tape and jointing compound of India Gypboard Ltd. and providing necesary plaster of paris putty. |     |      |      |        |
|       | After preparing the surface,Gypboard surface has to be painted with two coats of emulsion of approved make and shade over a coat of primer. Rate shall include making necessary cuttings for light fittings AC diffusers and other fixtures. No deductions shall be made for the opening and no extra payment made for forming any opening up to 0.5 sqm(per opening)                                                                                                                                                                                                                                                                                                                                                               |     |      |      |        |
|       | The work shall be carried out as per the manufactures specififcations using cold rolled Gypsteel and Sypsum boards manufactured by Gypsum India Ltd.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                |     |      |      |        |
|       | FINISHED PLAN AREA , EXCLUDING THE VERTICAL DROPS WILL BE MEASURED FOR PAYMENT.                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                     |     |      |      |        |

| Sl.No     | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                | Qty | Unit     | Rate | Amount      |
|-----------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----------|------|-------------|
| <b>b)</b> | <b>Mineral Fibre Grid Ceiling</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                          |     |          |      |             |
|           | Providing and fixing Mineral Fibre Grid False Ceiling System with reveal edge. The frame work made out of hot dipped galvanized steel section, rotary stitched main tee of size 15mm x 42 mm web height, having 0.36 mm gauge at every 600 mm centre to centre maximum and rotary stitched cross tee of size 15 mm x 42 mm, having 0.33 mm gauge at every 600 mm. c/c. and wall angle of size 19 x 19 mm., having 0.35 mm gauge fixed to the periphery of the wall. The above grid is suspended at every 600mm c/c. in both directions using 2.0 mm. thick pre-straightened GI wire laying fine fissured micro look with silhouette grid ceiling tiles of size 595mmx595mmx15mm having NRC 0.55, surface having 3 coats of white paint with Fine Fissured, back of the tile duly sanded and finished with a coat of protective paint all etc. complete as directed by the Bank's Engineers | 54  | Sq. Mts. |      | 0.00        |
|           | <b>TOTAL</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                               |     |          |      | <b>0.00</b> |
|           |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |     |          |      |             |
| <b>B</b>  | <b>ATM</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                 |     |          |      |             |
| <b>1</b>  | <b>ACP covering for Rolling shutter &amp; panelling DB wall</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |     |          |      |             |

| Sl.No    | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    | Qty | Unit     | Rate | Amount |
|----------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----------|------|--------|
|          | Supplying and fixing Aluminium framework using 25mm x50 mm x1.5 mm square aluminium sections in the front, sides and bottom of rolling shutter and covering with 3mm ACP of approved colour on the sides that are visible. The bottom panel should be hinged and openable for maintenance of Rolling Shutters and also doors to be provided on the panelling for controlling DB. The rates shall be including all accessories SS hinges, SS handles, ballcatches, etc., complete.                                                                              | 16  | Sq. Mts. |      | 0.00   |
| <b>2</b> | <b>Frameless Entrance Door - 12mm thick toughened glass</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                    |     |          |      |        |
|          | Providing and fixing 210 cm high 12mm thick toughened glass (SAINT GOBAIN or MODIGUARD) Entrance Door using patch fittings .Rubber beading to be given to the doors. Doors to be provided with 25mm x 425mm SS handles(H type) , Glass door to door Patch Lock with strike box (without glass cutting) and heavy duty floor spring with double swing control (Dorma 75V or equivalent) supporting 80 kg. Door opening size:-90 cm x 210 cm . Vinyl Film strips of frosted glass finish to be pasted on the glass as per design along with Logo of Canara Bank. | 2   | Sq. Mts. |      | 0.00   |
| <b>3</b> | <b>Frameless fixed glazing on the side of entrance door - 12mm thick toughened glass and front of Managers Cabin</b>                                                                                                                                                                                                                                                                                                                                                                                                                                           |     |          |      |        |
|          | Providing and fixing 210 cm high 12mm thick toughened glass (SAINT GOBAIN or MODIGUARD) fixed with patch fittings.                                                                                                                                                                                                                                                                                                                                                                                                                                             | 2   | Sq. Mts. |      | 0.00   |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                             | Qty | Unit     | Rate | Amount |
|-------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|----------|------|--------|
| 4     | <b>Double skin partitions above entrance partition/door</b>                                                                                                                                                                                                                                                                             |     |          |      |        |
|       | Providing and fixing Double skin partitions above 210cm level upto bottom of true ceiling using aluminium frame work of size :- 50mm x 50mm x 2mm (2 ft'c/c) bothways covered on both sides with 6 mm BWR 303 grade plywood finished with 1mm lamination of approved colour & pattern as per the design given in the drawing.           | 2   | Sq. Mts. |      | 0.00   |
|       |                                                                                                                                                                                                                                                                                                                                         |     |          |      |        |
| 5     | <b>Single level Gypboard false ceiling at + 240 lvl</b>                                                                                                                                                                                                                                                                                 |     |          |      |        |
|       | Providing and fixing Single level suspended false ceiling with Gypboard of 12.5mm thick to the suspended grid formed of perimeter channel of size 20 x 27 x30 mm (MF6A) and intermediate channel of size 45 x 15 x 0.9 mm (MF7)                                                                                                         | 6   | Sq. Mts. |      | 0.00   |
|       | The G.I. Ceiling section of size 80 x26x0.5 mm (MF .5) shall be provided across the intermediate channel at intervals not more than 475 mm c/c at bottom and the same shall be fixed by GI connections clips of 2.64mm dia at integration points.                                                                                       |     |          |      |        |
|       | The Ceiling channels shall be provided with a minimum overlap of 150mm at ends and fixed to the perimeter channels. The suspended strap hangers to be connected with G.I soffit cleat of size 37 x27x25x1.5 mm thick and to be fixed on to the roof slabs/beams by using metal expansion fasteners of 12.5 mm dia to a length of 35 mm. |     |          |      |        |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Qty  | Unit     | Rate | Amount |
|-------|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------|----------|------|--------|
|       | The suspender supporters shall be provided at intervals not more than 1200 mm c/c Additional perimeter channels have to be provided around the cut for light fitting A/C diffusers etc. Additional support for cut outs to be provided at no extra cost. The Gypboard shall be fixed top the inner side of the suspended grid by using 25mm long dry wall screws. The joints shall be finished with joint paper tape and jointing compound of India Gypboard Ltd. and providing necessary plaster of paris putty. |      |          |      |        |
|       | After preparing the surface, Gypboard surface has to be painted with two coats of emulsion of approved make and shade over a coat of primer. Rate shall include making necessary cuttings for light fittings AC diffusers and other fixtures. No deductions shall be made for the opening and no extra payment made for forming any opening up to 0.5 sqm(per opening)                                                                                                                                            |      |          |      |        |
|       | The work shall be carried out as per the manufactures specifications using cold rolled Gypsteel and Sypsum boards manufactured by Gypsum India Ltd.                                                                                                                                                                                                                                                                                                                                                               |      |          |      |        |
|       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |      |          |      |        |
|       |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |      |          |      |        |
| 6     | <b>Composite Partition including Doors (one side plywood with laminate and one side Cement Board painted)</b>                                                                                                                                                                                                                                                                                                                                                                                                     | 5.00 | Sq. Mts. |      | 0.00   |

| Sl.No | Description                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                             | Qty | Unit | Rate | Amount      |
|-------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-----|------|------|-------------|
|       | Providing & fixing composite partitions as per design with Rectangular Aluminium sections of 50mm x 50mm x 2mm size provided at not more than 600 mm c/c both ways and covered on one side with 3 mm thick ACP sheet and the other side 6 mm thick Cement board using self drilling screws between banking hall and back office area, etc. The partition should withstand its weight. TTthe Joints between the Cement board shall be fixed with fiberglass joint mesh and finished with putty.                                                                                                                                                                                                                                                          |     |      |      |             |
|       | Provision for flush door 60 cms wide shall be considered wherever required. Additional stiffners using 18 mm thick 303 Grade (BWR) plywood shall be made for fixing flush shutters.Doors to be provided with Vision Glass 6mm thick of 30cms x 90 cms, heavy duty Door closers (EBCO/Godrej /DORMA ), cylindrical lock ( EBCO/Godrej /DORMA ) , SS Tower bolts as per instructions etc. Complete. Vinyl Film strips of frosted glass finish to be pasted as per design on the glass. (The partition shall be erected upto 3" above the False Ceiling Level and the corner / and third vertical supports shall be anchored firmly to the RCC roof for support. However, only the exposed area below the False Ceiling shall be considered for payment.). |     |      |      |             |
|       | <b>TOTAL</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                            |     |      |      | <b>0.00</b> |
|       | <b>GRAND TOTAL (BANKING AREA+ ATM)</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                  |     |      |      | <b>0.00</b> |
|       | <b>ADD 18% GST</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                      |     |      |      | <b>0.00</b> |
|       | <b>TOTAL INCLUDING GST</b>                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                              |     |      |      | <b>0.00</b> |